MICHIGAN 1:62,500

WAR DEPARTMENT
CORPS OF ENGINEERS, U. S. ARMY

FIRST EDITION-AMS 1

LAINGSBURG QUADRANGLE
15 MINUTE SERIES

(PERRINTON) (ELSIE) (CHESANING) (LANSING) (DE WITT) (CORUNNA) (FOWLERVILLE)

OVID
MIDDLEBURY
WOODHULL
BENNINGTON
VICTOR
SCIOTA
BATH
DELTA
MERIDIAN
WILLIAMSTON
LANSING

Wildcat Sch
Soule Sch
Marshall Sch
Merrill Sch
OAK GROVE CEMETERY
Jesse Sch
SOUTH OVID CEM
Hammond Sch
Bogus Sch
Wilson Sch
Warren Sch
Middlebury Church
Sherman Sch
Dennison Sch
Meridian Sch
Leland Sch
Price
Grove Sch
STILSON CEM
Montague Lake
Richmond Lake
Deyle Sch
School No. 5
Walters Sch
Blood Sch
Cedar Lake Sch
Giffels Sch
Laingsburg
Octagon Sch
Aldrich Sch
Reed Ch
Reed Sch
Morton Sch
Wert Sch
Pierson Sch
Round Lake
Leon Lake
Chant Sch
Clark Sch
Collister Sch
Sprague Sch
Graham Sch
Kay Sch
Rose Sch
Corkin Sch
Shaftsburg
Wallace Sch
Haynes Sch
Towar Gardens
Carl Sch
Pine Lake
Haslett
Harmon Sch

Maple River
Little Maple River
Looking Glass River
Vermillion Creek
Grand River
Central New York Railroad
Pere Marquette Railroad
Consumers Power Line
Chandler Ditch
Remey Ditch

Clinton Shiawassee Co
Ingham Co

T7N T6N T5N T4N
R2W R1W R1E R2E

(ELSIE) OVID 0.5 MI. OVID 1.0 MI. CARLAND 5.0 MI. OWOSSO 5.0 MI. BENNINGTON 0.4 MI. E. LANSING 1.0 MI. LANSING 5.1 MI. U.S. RT. 16 1.7 MI. OKEMOS 2.7 MI. (MASON) WILLIAMSTON 4.0 MI. LANSING 2.3 MI. GUNNISONVILLE 1.2 MI. STATE RT. 47 1.6 MI.

First Edition (AMS 1) 1944.

Prepared under the direction of the Chief of Engineers, U. S. Army, by the Army Map Service (SU), U. S. Army, Washington, D. C., 1944.
Based on U.S.G.S. quadrangle, Laingsburg, 1:62,500 (1928).
Control by U.S. Geological Survey.
Surveyed in cooperation with the State of Michigan, 1921-25-26.
Revised from controlled Mosaic (SA) Newark, N. J.
Aerial photography by A.A.A. Department of Agriculture, 1938-1940.
Polyconic Projection, North American Datum.

ROAD CLASSIFICATION 1940

Dependable hard-surface, heavy-duty road.
Loose-surface graded, dry weather road.
U. S. Route 160
Secondary, hard-surface, all-weather road.
Dirt road.
State Route 30
More than two lanes indicated by note along road with tick at point of change. 3 LANE | 4 LANE

Scale 1:62,500

1 0 1 2 3 Miles
1000 0 1000 2000 3000 4000 5000 Yards

CONTOUR INTERVAL 10 FEET
DATUM IS MEAN SEA LEVEL

FIVE THOUSAND YARD GRID COMPUTED FROM "GRID SYSTEM FOR PROGRESSIVE MAPS IN THE U.S." ZONE B, U.S.C. & G.S. SPECIAL PUBLICATION NO. 59
THE LAST THREE DIGITS OF THE GRID NUMBERS ARE OMITTED
MICHIGAN STATE GRID ZONE EAST, IS INDICATED BY DOTTED TICKS OUTSIDE THE NEAT LINE AT 10,000 FOOT INTERVALS.
NOTE: OFFICERS USING THIS MAP WILL MARK HEREON CORRECTIONS AND ADDITIONS WHICH COME TO THEIR ATTENTION AND MAIL DIRECT TO "THE CHIEF OF ENGINEERS, WASHINGTON, D. C."

USGS
Historical File
Topographic Division

APPROXIMATE MEAN DECLINATION 1944
FOR CENTER OF SHEET
ANNUAL MAGNETIC CHANGE 1° DECREASE

Use diagram only to obtain numerical values. To determine magnetic north line, connect the pivot point "P" on the south edge of the map with the value of the angle between GRID NORTH and MAGNETIC NORTH, as plotted on the degree scale at the north edge of the map.

ARMY MAP SERVICE, U.S. ARMY, WASHINGTON, D.C., 111183
1944
10/44 SX

U. S. G. S.
FILE COPY
Inspection and Editing

LAINGSBURG, MICH.
N4245-W8415/15