

Topography by planetable surveys 1940. Revised 1967

Selected hydrographic data compiled from U.S. Lake Survey Charts 41 and 412 (1966). This information is not intended for navigational purposes

Polyconic projection. 1927 North American datum 10,000-foot grid based on Michigan coordinate system, south zone 1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue

Red tint indicates areas in which only landmark buildings are shown

Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked UTM GRID AND 1967 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

3° 53 MILS 1°28' 26 MILS

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D.C. 20242 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

CONTOUR INTERVAL 5 FEET DATUM IS MEAN SEA LEVEL DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS RIVER SURFACE AT FOLLOWING STAGES: LAKE ST. CLAIR 571.7 AND LAKE ERIE 568.6

QUADRANGLE LOCATION

MICHIGAN

WYANDOTTE, MICH. - ONT. N4207.5-W8307.5/7.5

3540

NOV 2 4 1969

1967 AMS 4368 II NW-SERIES V862