

Topography by photogrammetric methods from aerial photographs taken 1965. Field checked 1968

Polyconic projection. 1927 North American datum 10,000-foot grid based on Minnesota coordinate system, south zone 1000-meter Universal Transverse Mercator grid ticks, zone 15, shown in blue

Fine red dashed lines indicate selected fence and field lines where UTM GRID AND 1968 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET generally visible on aerial photographs This information is unchecked

5½°

0°13' 98 MILS

Primary highway, all weather, Light-duty road, all weather, 1000 2000 3000 4000 5000 6000 7000 FEET hard surface_____ improved surface_____ 1 KILOMETER Secondary highway, all weather, Unimproved road, fair or dry .5 hard surface weather _____ CONTOUR INTERVAL 10 FEET U. S. Route State Route DATUM IS MEAN SEA LEVEL MINN. ZUMBROTA, MINN. QUADRANGLE LOCATION THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS N4415-W9237.5/7.5 FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST 1968

....

NOV 5 - 1970

University of Manasia

to a d

....

AMS 7472 I SW-SERIES V872